



High Power Amplifier

Model:RPA-800M-2G-316

800-2000MHz 316W CW

Ultrabroad frequency range, high performance and exceptional RF characteristics

Features:

- Frequency range: 800-2000MHz
- High output power at saturation, 55dBm Typ
- High gain, 56dB Min
- Operates from AC line power: 110-220V

Applications:

- Laboratory test instrument
- RF Power stress test
- EMI and antenna testing
- Reliability testing

Product Overview:

The RPA-800M-2G-316 is a high power, rack mount amplifier with a self-contained AC power supply which can be used for a wide variety of laboratory testing applications. This rugged amplifier is capable of amplifying signals up to 316W output power over its entire operating bandwidth of 800 to 2000MHz. The control functions RPA-800M-2G-316 possesses include the on/off of the power supply and output power can be controlled by the automatic ALC system. Built-in safety features include fans alarms and automatic shut down mechanism to prevent damage in the event of excessive internal temperatures. The amplifier's output stage is further protected in the event of a fault condition, allowing high power operation for up to 5 minutes into an open or short load (refer to the maximum input power specifications). And it has built-in protection functions included over TEM, over voltage, over current and over VSWR protection. It can also be remotely controlled via RS422 or Ethernet.



Electrical Specifications at 25°C:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	800-2000			MHz
Power Gain	GP	56	58		dB
Gain flatness	Δ GL		± 2	± 2.5	dB
Output Psat	Psat		55		dBm
Output P1dB	P1dB	52	53		dBm
Spurious	Spur			-60	dBc
Harmonics	HAM			-10	dBc
Input VSWR	VSWRin		1.5	2.0	:1
AC Voltage	Vac	110	220		V AC
AC Supply Current	Iac		8		A
Impedance	I/O-IMP	50			Ohms

Mechanical Specifications:

Parameter	Value	Notes
Operating Temperature	-20 to +40	°C
Non-operating Temperature	-30 to +60	°C
Relative humidity	95	%
RF Input/Output Connector	N Female/N Female	
Digital Monitor & Control	RS422;Ethernet	
Cooling	Built in Cooling system,forced air cooling	
Altitude	10,000	feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis	
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions	
Dimensions W x H x D	482.6*133.2*447	mm
Weight	15	Kg

Absolute Maximum Ratings:


Parameter	Value
RF Input Power	0 dBm
ESD sensitivity (HBm)	Class 0, passed 150V



Outline Drawing:

Unit:mm

RPA-800M-2G-316





Optional items:

Number	Parameter
1	LCD display touchscreen
2	Ingress protection grad
3	Customized operating temperature range
4	Built in Cooling system(air or liquid)
5	Types of RF,coupling and monitor&control interfaces

Ordering Information:

Base Number	Description	Optional
RPA-800M-2G-316	High Power Amplifier, 800-2000MHz, 316W CW, Built in air or liquid cooling, without LCD and IP grad.	Basic version
RPA-800M-2G-316-M	High Power Amplifier, 800-2000MHz, 316W CW, Built in air or liquid cooling, with LCD.	Add LCD display touchscreen
RPA-800M-2G-316-IPxx	High Power Amplifier, 800-2000MHz, 316W CW, Built in air or liquid cooling, with LCD and IP grad.	Add Ingress protection grad