



Low Noise Amplifier

Model: LNA18G27G-5228

18-27GHz 52dB, Gain 2.8dB, NF

Ultrabroad frequency range, high small signal gain, low noise figure and good gain flatness

Features:

- Frequency range: 18-27GHz
- Small Signal Gain: 52dB min.
- Output P1dB: 8dBm min.
- Noise Figure: 2.8dB max.
- Operating voltage/current: +12 VDC/200mA.
- Simple 220V system available SAC option.
- 50 Ohm Matched Input / Output.

Applications:

- Laboratory Applications
- R&D Labs
- Radar Systems
- ISM
- Test Instrumentation

Product Overview:

The LNA18G27G-5228 is a coaxial low noise operating in the 18 to 27 GHz frequency range. The amplifier offers a maximum noise figure of 2.8 dB, 8 dBm minimum of output P1dB and a minimum small signal gain of 52 dB with the excellent gain flatness of ± 0.6 dB nominal. The DC power requirement for the amplifier is +12 VDC/200 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.



Electrical Specifications at 25°C:

Parameter	Min	Typ	Max	Units
Frequency range	18		27	GHz
Small Signal Gain	52			dB
Small Signal Gain Flatness		±0.6		dB
Noise Figure			2.8	dB
Output P1dB	8			dBm
Input VSWR			2	:1
DC Voltage		+12		V DC
DC Supply Current		200		mA
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value	Notes
Operating Temperature	-40°C to +70°C	
Non-operating Temperature	-55°C to +85°C	
Relative humidity	95	%
RF Input/Output Connector	2.92mm Female/2.92mm Female	
DC Bias	Solder Pin	
Altitude	10,000	feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis	
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions	
Dimensions W x H x D	44.8 x 29.2 x 11	mm


Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	TBD
RF Input Power	TBD
ESD sensitivity (HBm)	Class 0, passed 150V



Outline Drawing:

Unit:mm; Tolerance:±0.1mm



Ordering Information:

Base Number	Description	Optional
LNA18G27G-5228	Low Noise Amplifier, 18-27GHz, Gain:52dB,Noise Figure:2.8dB,P1dB:8dBm,+12V DC	Without Heatsink
LNA18G27G-5228-HS	Low Noise Amplifier, 18-27GHz, Gain:52dB,Noise Figure:2.8dB,P1dB:8dBm,+12V DC	With Heatsink